

1

2

3

4

5

6

7

8

THIS DRAWING AND THE DATA DISCLOSED HEREIN OR HEREWITH IS NOT TO BE REPRODUCED USED OR DISCLOSED IN WHOLE OR IN PART TO ANYONE WITHOUT THE PERMISSION OF JESS—LINK PRODUCTS CO.,LTD.(JPC)

CUSTOMER DRAWING  
DRWC—000556

| REV. | ECN NO. | DESCRIPTION           | MDF'D    | APP'D   | DATE       |
|------|---------|-----------------------|----------|---------|------------|
| 01   |         | INITIAL DESIGN        | denghong | RICHARD | 07/09/2020 |
| A1   |         | 更換新圖框, 正式版發行.         | denghong | RICHARD | 07/30/2021 |
| A2   |         | 修改備註第二條, 增加額定電流的適用線徑. | denghong | RICHARD | 02/28/2022 |

A

B

C

D

E

F

Standard part List(WITH HVIL)  
產品型號表(帶護鎖)

| Model No.    | JPC No.        | Accepted Wire OD |
|--------------|----------------|------------------|
| TL28X-201-25 | PCNTC111RC78-0 | 13.2~14.0        |
| TL28Y-201-25 | PCNTC211RC78-0 |                  |
| TL28U-201-25 | PCNTC311RC78-0 |                  |
| TL28V-201-25 | PCNTC411RC78-0 |                  |
| TL28W-201-25 | PCNTC511RC78-0 |                  |
| TL28T-201-25 | PCNTC611RC78-0 |                  |
| TL28X-201-35 | PCNTC112RC78-0 | 14.2~15.0        |
| TL28Y-201-35 | PCNTC212RC78-0 |                  |
| TL28U-201-35 | PCNTC312RC78-0 |                  |
| TL28V-201-35 | PCNTC412RC78-0 |                  |
| TL28W-201-35 | PCNTC512RC78-0 |                  |
| TL28T-201-35 | PCNTC612RC78-0 |                  |
| TL28X-201-50 | PCNTC113RC78-0 | 16.7~17.5        |
| TL28Y-201-50 | PCNTC213RC78-0 |                  |
| TL28U-201-50 | PCNTC313RC78-0 |                  |
| TL28V-201-50 | PCNTC413RC78-0 |                  |
| TL28W-201-50 | PCNTC513RC78-0 |                  |
| TL28T-201-50 | PCNTC613RC78-0 |                  |

Standard part List(WITHOUT HVIL)  
產品型號表(不帶護鎖)

| Model No.    | JPC No.        | Accepted Wire OD |
|--------------|----------------|------------------|
| TL28X-200-25 | PCNTC101RC78-0 | 13.2~14.0        |
| TL28Y-200-25 | PCNTC201RC78-0 |                  |
| TL28U-200-25 | PCNTC301RC78-0 |                  |
| TL28V-200-25 | PCNTC401RC78-0 |                  |
| TL28W-200-25 | PCNTC501RC78-0 |                  |
| TL28T-200-25 | PCNTC601RC78-0 |                  |
| TL28X-200-35 | PCNTC102RC78-0 | 14.2~15.0        |
| TL28Y-200-35 | PCNTC202RC78-0 |                  |
| TL28U-200-35 | PCNTC302RC78-0 |                  |
| TL28V-200-35 | PCNTC402RC78-0 |                  |
| TL28W-200-35 | PCNTC502RC78-0 |                  |
| TL28T-200-35 | PCNTC602RC78-0 |                  |
| TL28X-200-50 | PCNTC103RC78-0 | 16.7~17.5        |
| TL28Y-200-50 | PCNTC203RC78-0 |                  |
| TL28U-200-50 | PCNTC303RC78-0 |                  |
| TL28V-200-50 | PCNTC403RC78-0 |                  |
| TL28W-200-50 | PCNTC503RC78-0 |                  |
| TL28T-200-50 | PCNTC603RC78-0 |                  |

ø29.00

62.60±0.25

27.9

101.5 REF

扭矩標識需清晰

CAP

Ordering Information

訂購信息

TL28 X - 201 - 25

鍵位及顏色 Key&Color

"X" 橙色 Orange

"Y" 黑色 Black

"U" 黃色 Yellow

"V" 綠色 Green

"W" 紅色 Red

"T" 藍色 Blue

高壓互鎖 HVIL

0,不帶互鎖 No HVIL

1,帶互鎖 With HVIL

線纜大小 Cable Size

"25"=25mm<sup>2</sup>

"35"=35mm<sup>2</sup>

"50"=50mm<sup>2</sup>

M方向鍵位示意圖

X

Y

U

V

W

T

RoHS COMPLIANT

HALOGEN FREE

Unit : mm

GENERAL TOLERANCES:  
(UNLESS SPECIFIED)

0 = ±.50

0.0 = ±.25

0.00 = ±.15

0.000 = ±.05

0" = ± 2"

0.0" = ± 1"

PROJECTION

D.R. 02/28/2022  
denghong

CH.K

APV.D

JPC connectivity

TITLE

TL200 1POS PLUG RA TYPE

SCALE 1:1

SHEET 1 OF 1

PD./FILE NO. C20C0017A

REV. A2

1

2

3

4

5

6

7

8