








THIS DRAWING AND THE DATA DISCLOSED HEREIN OR HEREWITH IS NOT TO BE REPRODUCED USED OR  
DISCLOSED IN WHOLE OR IN PART TO ANYONE WITHOUT THE PERMISSION OF JESS-LINK PRODUCTS CO.,LTD.(JPC)


## CUSTOMER DRAWING

REV.	ECN NO.	DESCRIPTION	MDF'D	APP'D	DATE
01		INITIAL DESIGN	Colin	Andrew	11/12/2020
02		UPDATE DATE	Colin	Andrew	03/18/2021



### NOTE:

- 儲存溫度Storage temperture:  $-40^{\circ}\text{C} \sim +80^{\circ}\text{C}$
- 工作溫度Operating temperature:  $-40 \sim +125^{\circ}\text{C}$
- 額定電流Current rating: 隨保險絲(Fuse)規格而變動;
- 額定電壓Operating voltage: Power: DC750V;
- 防護等級(連接狀態)Protection class: IP67&IP6K9K;
- 絕緣材料阻燃等級Flame retardant grade of insulating materials: UL94V-0;
- 使用壽命: Durability: 50cycle;
- 帶高壓互鎖Electrical interlock: (HVIL);
- 安裝板厚度: 最大5mm

RoHS COMPLIANT	HALOGEN FREE	Unit : mm	PROJECTION 		JPC connectivity			
		GENERAL TOLERANCES: (UNLESS SPECIFIED)	D.R.	03/18/2021				
		0 = ±.50 0.0 = ±.25 0.00 = ±.15 0.000 = ±.05 0" = ±.2" 0.0" = ±.1"	Colin	CH.K				
			APV.D		SCALE	SIZE	DWG NO.	REV. 02
					1:2	A4	PCN2C001RC78-0	SH,T NO. 1 OF 1