


鍵位示意圖



JPCXLP182	*	— 2.0 *	— 50
鍵位	高壓互鎖	線纜大小	
"A"	0:不帶互鎖	"25"=25mm	
"B"	1:帶互鎖	"35"=35mm	
"C"		"50"=50mm	

- 規格參數:
- 1.工作溫度Operating temperature: -40°C~+125°C.
  - 2.額定電流Current rating:Power:200A.
  - 3.額定電壓Operating voltage:Power:1000VDC.
  - 4.耐電壓Dielectric withstanding voltage:5000VDC.
  - 5.防護等級Protection class:IP67(mated).
  - 6.電磁Shielding:
  - 7.機械壽命Mating cycle:100Min.
  - 8.帶自動二次鎖扣Automatic secondary lock.
  - 9.帶高壓互鎖Electrical interlock(HVIL可選擇)
  - 10.配對插座Mating receptacle:PD8FA10X02W1-0/PD8FA10X02W2-0

Standard Part List(With HVIL)		
Model NO.	JPC NO.	Accepted Wire Size
JPCXLP182A-201-25	PD8MA14X02W0-0	13.5~13.8 (屏蔽線)
JPCXLP182B-201-25	PD8MB14X02W0-0	
JPCXLP182C-201-25	PD8MC14X02W0-0	
JPCXLP182A-201-35	PD8MA15X02W0-0	14.5~15.0 (屏蔽線)
JPCXLP182B-201-35	PD8MB15X02W0-0	
JPCXLP182C-201-35	PD8MC15X02W0-0	
JPCXLP182A-201-50	PD8MA16X02W0-0	17.0~17.5 (屏蔽線)
JPCXLP182B-201-50	PD8MB16X02W0-0	
JPCXLP182C-201-50	PD8MC16X02W0-0	

Standard Part List(Without HVIL)		
Model NO.	JPC NO.	Accepted Wire Size
JPCXLP182A-200-25	PD8MA04X02W0-0	13.5~13.8 (屏蔽線)
JPCXLP182B-200-25	PD8MB04X02W0-0	
JPCXLP182C-200-25	PD8MC04X02W0-0	
JPCXLP182A-200-35	PD8MA05X02W0-0	14.5~15.0 (屏蔽線)
JPCXLP182B-200-35	PD8MB05X02W0-0	
JPCXLP182C-200-35	PD8MC05X02W0-0	
JPCXLP182A-200-50	PD8MA06X02W0-0	17.0~17.5 (屏蔽線)
JPCXLP182B-200-50	PD8MB06X02W0-0	
JPCXLP182C-200-50	PD8MC06X02W0-0	

RoHS COMPLIANT

HALOGEN FREE

Unit : mm

GENERAL TOLERANCES: (UNLESS SPECIFIED)

0 = ±.50

0.0 = ±.25

0.00 = ±.15

0.000 = ±.05

0° = ± 2°

0.0° = ± 1°

PROJECTION

D.R. 05/15/2022 Chunxia

CH.K 05/15/2022 Andrew

APV.D 05/15/2022 Richard

JPC connectivity

JPCXLP200插頭

SCALE NA

SIZE A4

PART NO. PD8MA14X02W0-0

PD./FILE NO. ---

REV. 01

SHEET 1 OF 1