THIS DRAWING AND THE DATA DISCLOSED HEREIN OR HEREWITH IS NOT TO BE REPRODUCED USED OR DISCLOSED IN WHOLE OR IN PART TO ANYONE WITHOUT THE PERMISSION OF JESS-LINK PRODUCTS CO.,LTD.(JPC)

CUSTOMER DRAWING

DRWC-003169

REV.	ECN NO.	DESCRIPTION	MDF'D	APP'D	DATE
01	---	INITIAL DESIGN	Chunxia	Richard	05/15/2022









訂購信息 Ordering Informating

JPCXLP182 A — 61 — 2.5

- A: 鍵位 "A" "B" "C" "D" "E" "F"
- 61: 高壓互鎖 0:不帶互鎖 1:帶互鎖
- 2.5: 線纜大小 "2.5"=2.5mm²

規格參數:

1.工作溫度Operating temperature:-40°C~125°C.
2.額定電流Current rating:23A(Max).
3.額定電壓Operating voltage:600VAC.
4.耐電壓Dielectric withstanding voltage:3000VAC.
5.防護等級Protection class:IP67(mated).
6.機械壽命Mating cycle:100Min.
7.鎖扣類型Latching style:Two stage,finger actuated.
8.帶高壓互鎖Electrical interlock(HVIL可選擇)
9.屏蔽Shielding:360°From wire to device(互配).
10.配對插座Mating plug:PD8FA11X02W0-0

Standard part List(HVIL)			Standard part List(Without HVIL)		
Model NO.	JPC NO.	Accepted Wire Size	Model NO.	JPC NO.	Accepted Wire Size
JPCXLP182A-61-2.5	PD8MA01X02W0-0	2.5mm²非屏蔽線 Ø5.0m~5.4m	JPCXLP182A-60-2.5	PD8MA11X02W0-0	2.5mm²非屏蔽線 Ø5.0m~5.4m
JPCXLP182B-61-2.5	PD8MB01X02W0-0		JPCXLP182B-60-2.5	PD8MB11X02W0-0	
JPCXLP182C-61-2.5	PD8MC01X02W0-0		JPCXLP182C-60-2.5	PD8MC11X02W0-0	
JPCXLP182D-61-2.5	PD8MD01X02W0-0		JPCXLP182D-60-2.5	PD8MD11X02W0-0	
JPCXLP182E-61-2.5	PD8ME01X02W0-0		JPCXLP182E-60-2.5	PD8ME11X02W0-0	
JPCXLP182F-61-2.5	PD8MF01X02W0-0		JPCXLP182F-60-2.5	PD8MF11X02W0-0	

RoHS COMPLIANT

HALOGEN FREE

Unit : mm

GENERAL TOLERANCES: (UNLESS SPECIFIED)
0 = ±.50
0.0 = ±.25
0.00 = ±.15
0.000 = ±.05
0° = ± 2°
0.0° = ± 1°

PROJECTION

D.R. 05/15/2022 Chunxia
CH.K 05/15/2022 Andrew
APV.D 05/15/2022 Richard

JPC connectivity

TITLE: JPCXLP602插頭

PD./FILE NO.: ---

SCALE: 1:1 | SIZE: A4 | PART NO.: PD8MA01X02W0-0 | REV. 01 | SHEET 1 OF 1