






THIS DRAWING AND THE DATA DISCLOSED HEREIN OR HEREWITH IS NOT TO BE REPRODUCED USED OR DISCLOSED IN WHOLE OR IN PART TO ANYONE WITHOUT THE PERMISSION OF JESS-LINK PRODUCTS CO.,LTD.(JPC)

# CUSTOMER DRAWING

DRWC-003170

REV.	ECN NO.	DESCRIPTION	MDF'D	APP'D	DATE
01	---	INITIAL DESIGN	Chunxia	Richard	05/15/2022



M方向鍵位示意圖

## Standard Part List

Model NO.	JPC NO.	Polarization	Cable Size(mm <sup>2</sup> )
XL183X-200-2.5	PD8MX01X03W0-1	X	2.5
XL183Y-200-2.5	PD8MY01X03W0-1	Y	2.5
XL183Z-200-2.5	PD8MZ01X03W0-1	Z	2.5
XL183W-200-2.5	PD8MW01X03W0-1	W	2.5
XL183N-200-2.5	PD8MN01X03W0-1	N	2.5
XL183X-200-4	PD8MX02X03W0-1	X	4
XL183Y-200-4	PD8MY02X03W0-1	Y	4
XL183Z-200-4	PD8MZ02X03W0-1	Z	4
XL183W-200-4	PD8MW02X03W0-1	W	4
XL183N-200-4	PD8MN02X03W0-1	N	4

## 規格參數:

- 1.工作溫度Operating temperature:-40°C~+125°C.
- 2.額定電流Current rating:2.5mm<sup>2</sup>:23A;4.0mm<sup>2</sup>:32A.
- 3.額定電壓Operating voltage:630VDC/400VAC.
- 4.耐電壓Dielectric withstanding voltage:4000VDC.
- 5.防護等級Protection class:IP67(mated).
- 6.機械壽命Mating cycle:100Min.
- 7.絕緣電阻Insulation resistance:2000MΩ Min(25°C)
- 8.配對插座Mating receptacle:PD8FX01X03W0-1

## 備註 (Note):

印字內容如下

XL183(-200-) YYWW

連接器型號

"YY"為年份，取後面兩位  
"WW"為周數

## 訂購信息 Ordering Informating

XL183X	— 200 —	XX
鍵位 "X" "Y" "Z" "W" "N"		線纜大小 "2.5"=2.5mm <sup>2</sup> "4"=4.0mm <sup>2</sup>

RoHS COMPLIANT	HALOGEN FREE	Unit : mm	PROJECTION D.R. 05/15/2022 Chunxia CH.K 05/15/2022 Andrew APV.D 05/15/2022 Richard	JPC connectivity			PD./FILE NO. ---
				TITLE	SCALE	SIZE	
		GENERAL TOLERANCES: (UNLESS SPECIFIED) 0 = ±.50 0.0 = ±.25 0.00 = ±.15 0.000 = ±.05 0" = ±.2" 0.0" = ±.1"		XL203插頭	NA	A4	
				PART NO. PD8MX01X03W0-1			REV. 01 SHEET 1 OF 1