



佳必琪國際股份有限公司 JESS-LINK PRODUCTS CO., LTD.

- Technology Exchange
- Project Management
- Integrated Solutions
- Time to Market
- Quality Driven
- Supply Assurance
- Customized Friendly
- Integrity and Respect



Smart Connection Industry



Industrial connector

Industrial Circular & Square series connector



Circular series

NO. of Contacts: 2-37 pin
 Rated Current: 1~80A
 Rated Voltage: 30~300V AC/DC
 Shell Size: 8, 9, 11, 15, 16, 17, 18, 19, 25, 30, 32, 40, 50
 Connector Type: Plug/Receptacle/Male/Female

Square series

NO. of Contacts: 2-26 pin
 Rated Current: 5~30A
 Rated Voltage: 250V AC/DC
 Shell Size: 20, 24, 28, 35, 41, 42
 Connector Type: Plug/Receptacle/Male/Female

Waterproof series connector



M8

NO. of Contacts: 3, 4pin
 Rated Current: 3A
 Rated Voltage: 60V AC/DC

RJ45 waterproof

Rated Current: 1.5A, 125V AC

M12

NO. of Contacts: 2~12 pin
 Rated Current: 1~4A
 Rated Voltage: 30~250V AC/DC
 A-code, D-code, X-code

*IP67 *Connector type: Plug/Receptacle/Male/Female

MIL-C-5015 series connector



MIL-C-5015 series (Commercial Versions)

Commercial Versions of Mil 5015
 NO. of Contacts: 2-54 pin
 Shell Size: 10SL~36
 Rated Current: 13~150A
 Rated Voltage: AC 200~3000V ; DC 250~4200V
 Connector Type: Straight Plug/Receptacle/Angled Plug/Cable Connecting Receptacle

Push pull circular series connector



Metal B series & Metal K series

Push-pull
 BS series – plug
 BR/BN series – fixed socket
 BF series – free socket
 2 to 32 pin


5000 mating cycles
 Working temp. -55 °C ~250°C
 Solder, DIP, crimp contacts
 Rated current 1.5~30A
 Finger-proof / 8~16 keyways

★ We also can offer customized cable assembly ★

Factory Automation Application

Factory Automation Market

Signal, Power, Motors, Electronics, Mechanical,
 Medical Equipment, MRT, Automobiles,
 Electric Vehicles, Communication Equipment



PRODUCT FEATURE

Shell Material: Material stability is not easy to deform.
 Insulating Material: Fireproof, High temperature and pressure resistant.
 Surface Treatment: High-tech surface with special matte finish, High-quality texture without reflection.
 Conductor(PIN): Well contact and Low impedance, Low temperature, Flat PIN, Stable impedance, Not easy to deteriorate.
 Cable Glands: Professional design and Tight fit, Waterproof.

Industrial cable

PLC and Servo cable




PLC Cable

mitsubishi / SIEMENS / KOYO / DELTA / FUJI /
 OMRON / Allen Bradley / KEYENCE /
 PANASONIC / NACHI / IDEC

Servo and others

Servo I/O cable / Servo encoder cable /
 Servo fiber cable / Servo motor power cable /
 Customized cable / Servo cable

Industrial Ethernet cable



Connector

M12 A-code/4pin/Plug male
 M12 D-code/4pin/Plug male
 M12 X-code/8pin/Plug male
 RJ45 Plug/Jack

Machine Vision cable



Vision cable

- MDR to MDR/MDR to SDR/26 pin (Maximum length:17 meters)
- USB 3.0 Vision Cables with Dual Screw Lock (Maximum length:5 meters)
- Ethernet Cables with Dual Screw Lock (Maximum length:25 meters)

Flexible Flat Cable & Flat Cable



Flexible Flat Cable

Bulk FFC
 FFC Multi-Port
 FFC Optional
 FFC Standard

High Temperature Series

IDC Cable assembly (125°C)
 PVC(125°C)
 TPE(125°C)

HDMI 2.1 AOC and USB AOC



Standard cables

AOC Cables: HDMI 2.0&2.1 USB 3.0/USB TYPE C

Customized OEM/ODM

Customized OEM/ODM : HDMI 2.1 & USB TYPE C Connectors and cables

Others

Proximity/Photoelectric Sensors Area Restrictions



Proximity sensors

Mini Cylindrical Metal Series
 Side Sensing Cylindrical Metal Barrel Series
 Cylindrical Metal Barrel Series
 Cuboid Plastic Series
 MPS Series
 Metal face Series
 High Temperature Series
 OCM Series

Photoelectric sensors

M18 Series
 T18 Series
 RP32 Series
 RP43 Series
 RP50 Series
 RP74 Series
 UP Series
 MP Series

Wire-saving Terminal Block Module Series



EtherCAT / CC-Link / Barrier&European Type Series

YAMAHA ROBOT Area Restrictions



YK-XE

YK-TW

YK-XG

YK-XGS

YK-XGP