

Push Pull Circular Connector	Product Type	Number of Contacts	Material	Connector Type (Plug/Receptacle)	Contact Gender (Male/Female)	Alignment Key	Backshell (Straight/Right Angle)	Termination	Mating Style	IP Rating	Operating Temperature Range
	1P Plastic series	2-14 pin	Plastic	Plug / Receptacle	Male /Female	0°/40°/60°/80°/170°/190°/205°	Straight / Right Angle	Solder, PCB type	Snap Latch	IP50	PSU: -50~150°C PEI: -50~170°C
	2P Plastic series	2-34 pin	Plastic	Plug / Receptacle	Male /Female	60°/80°/90°/100°/130°	Straight / Right Angle	Solder, PCB type	Snap Latch	IP50	PSU: -50~150°C PEI: -50~170°C
	B Metal series	2-32 pin	Metal	Plug / Receptacle	Male /Female	0°/30°/60°/90°/135°/190°/225°	Straight / Right Angle	Solder, PCB type	Snap Latch	IP67	-50~250°C
	K Metal series	2-32 pin	Metal	Plug / Receptacle	Male /Female	0°/30°/45°/60°/90°/120°/145°/220°/240°	Straight / Right Angle	Solder, PCB type	Snap Latch	IP67	-50~200°C
	S Metal series	2-6 pin	Metal	Plug / Receptacle	Male /Female	N/A	Straight / Right Angle	Solder, PCB type	Snap Latch	IP67	-50~250°C