

Industrial Circular Connector	Shell Size	Number of Contacts	Material	Connector Type (Plug/Receptacle)	Contact Gender (Male/Female)	Rated Current	Rated Voltage	Backshell (Straight/Right Angle)	Termination	Mating Style	Operating Temperature Range
	8	4, 5, 6	Metal	Plug / Receptacle	Male /Female	2A	125V AC	Straight	Solder	Push pull	-20~80℃
	9	4, 6, 7	Metal	Plug / Receptacle	Male /Female	1A	300V AC	Straight	Solder	Screw Thread / Bayonet	-20~80℃
	10	16	Metal	Plug / Receptacle	Male /Female	1A	30V AC	Straight	Solder	Screw Thread	-20~80℃
	11	10, 12, 16	Metal	Plug / Receptacle	Male /Female	1~2A	30~125V AC	Straight	Solder	Push pull	-20~80℃
	14	3, 4, 7	Metal	Plug / Adapter	Male /Female	5A	125V AC	Straight	Solder	Bayonet	-20~80℃
	15	2, 3, 4	Metal	Plug / Receptacle	Male /Female	5A	125V AC	Straight	Solder	Screw Thread	-20~80℃
	15.5	2, 4	Metal	Plug / Adapter	Male /Female	5A	125~150V AC	Straight	Solder	Screw Thread	-20~80℃
	16	2, 3, 4, 5, 6, 7, 8	Metal	Plug / Receptacle	Male /Female	5A	125V AC	Straight	Solder	Screw Thread	-20~80℃
	17	3,6	Plastic	Plug / Receptacle	Male /Female	5A	125V AC	Straight	Solder	Screw Thread	-20~80℃
	18	5, 7, 8	Metal	Plug / Receptacle	Male /Female	5A	125V AC	Straight	Solder	Screw Thread	-20~80℃
	19	2, 3, 4	Metal	Plug / Receptacle	Male /Female	7A	250V AC	Straight	Solder	Screw Thread	-20~80℃
	25	2, 3, 4, 5, 6	Metal	Plug / Receptacle	Male /Female	10A	250V AC	Straight	Solder	Screw Thread	-20~80℃
	25	3, 4	Plastic	Plug / Receptacle	Male /Female	10A	250V AC	Straight	Solder	Bayonet	-20~80℃
	30	2, 3, 4, 5, 7, 8	Metal	Plug / Receptacle	Male /Female	10~15A	250V AC	Straight	Solder	Screw Thread	-20~80℃
	31	4, 6	Metal	Plug / Receptacle	Male /Female	23~46A	500~900V AC	Straight	Solder	Bayonet	-20~80℃
	32	2, 3	Metal	Plug / Receptacle	Male /Female	30A	250V AC	Straight	Solder	Screw Thread	-20~80℃
	40	4, 8, 37	Metal	Plug / Receptacle	Male /Female	5~30A	250~300V AC	Straight	Solder	Screw Thread	-20~80℃
	50	4	Metal	Plug / Receptacle	Male /Female	80A	250V AC	Straight	Solder	Screw Thread	-20~80℃