

Industrial Square Connector	Shell Size	Number of Contacts	Material	Connector Type (Plug/Receptacle)	Contact Gender (Male/Female)	Rated Current	Rated Voltage	Backshell	Termination	Mating Style	Operating Temperature Range
	20	2, 3, 4, 5, 7, 12	Metal	Plug / Receptacle	Male /Female	5~15A	250V AC	Straight	Solder	Screw Thread	-20~80℃
	24	5, 10	Metal	Plug / Receptacle	Male /Female	10~15A	250V AC	Straight	Solder	Screw Thread	-20~80℃
	27	10	Plastic	Plug / Receptacle	Male /Female	5A	250V AC	Straight	Solder	Push Pull	-20~80℃
	28	3, 4, 7, 12, 16, 17, 20, 26	Metal	Plug / Receptacle	Male /Female	5~15A	250V AC	Straight	Solder	Screw Thread	-20~80℃
	35	24	Metal	Plug / Receptacle	Male /Female	8A	250V AC	Straight	Solder	Screw Thread	-20~80℃
	41	4, 8	Metal	Plug / Receptacle	Male /Female	15~30A	250V AC	Straight	Solder	Screw Thread	-20~80℃
	42	7, 37	Plastic	Plug / Receptacle	Male /Female	5~13A	250V AC	Straight	Solder	Screw Thread	-20~80℃